

DYNAMIC APPLICATION

PMXX® PLUS ENCODER&RESOLVER 9

APPLICATIVE FEATURES



UP TO 5 MILLION CYCLES
GUARANTEED CYCLES



UP TO 50 M/S2
ACCELERATION



UP TO 25,0 M
CABLE LENGTH



UP TO 300 M/MIN
TRAVEL SPEED



MINIMUM BENDING RADIUS

CROSS SECTION	CROSS SECTION MAX	DYNAMIC INSTALLATION	STATIC INSTALLATION
0,14	1,00	7 x Ø	5 x Ø

APPROVALS



AWM STYLE 21209
90°C 300V



AWM I/II A/B 90°C
300V



2014/35/CEE



IEC 60754-1
EN 50267-1



2011/65/UE
2015/863/UE



2014/30/EU

TECHNICAL DATA



STORAGE - 50°C + 90°C
DYNAMIC - 30°C + 90°C
STATIC - 40°C + 90°C



NOMINAL VOLTAGE 300 V
(UL/CSA)



TEST VOLTAGE C/C
2000VRMS,1MIN, C/OVERALL
SCREEN 2000VRMS,1MIN



INSULATION RESISTANCE ≥1
GOHM/KM

CONSTRUCTION FEATURES

GROUP 1	CONDUCTOR	CL6 EXTRA-FLEXIBLE. TINNED COPPER
	INSULATION	POLYPROPYLENE COMPOUND (PP)
	INSULATION COLOR	COLOURS SEQUENCE REFERS TO DIN 47100 STANDARD.
OVERALL STRANDING	FILLER	FILLER POLYPROPYLENE
	SEPARATIONLAYER	WRAPPING NON-WOVEN TAPE
	DRAINWIRE	DRAIN WIRE TINNED COPPER
	SCREEN	SCREEN TINNED COPPER 85 % ± 5 %
	SEPARATIONLAYER	OVERALL WRAPPING NON-WOVEN TAPE
	SHEATH	POLYURETHANE COMPOUND (TPU)
	SHEATH COLOUR	GREEN , RAL: 6018, DESINA: YES

PRODUCTS FEATURES



FIRE PERFORMANCE

SELF-EXTINGUISHING AND FLAME RETARDANT ACC. TO DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1-2, UL CABLE FLAME, UL VW-1, CSA FT1



OIL PERFORMANCE

VDE 0473-811-404, IEC 60811-404(EU), CEI EN 50363-10-2(EU), 1581(UL)



UV PERFORMANCE

ISO 4892-2, ASTM-D-2565-16, EN 50289-4-17



WATER PERFORMANCE

UL 1581, IEC 60811-1-3



COLD PERFORMANCE

EN 60811-1-4



ABRASION PERFORMANCE

ASTM D 4060



MUD PERFORMANCE

NEK 606



MICROBE PERFORMANCE

VDE 0282/10



HOZONE PERFORMANCE

EN 50396 ART. 8.1.3

TECO CODE	OEM REF.	FORMATION	CUT	ROLLS [M]	DRUMS [M]	EXT Ø [MM]	WEIGHT [KG/KM]
46702	INDRAMAT	(9X0,50)CCST (9XAWG21)CCST	✓	100	500	8.8	115

TE.CO. reserves the right to make changes to any of the products without, however, affecting the essential technical features. Unless specified otherwise, all the product ratings stated are nominal ratings. The RAL colour code is provided for illustrative purposes only.

Company managed and coordinated by Fangen S.r.l.. All rights reserved. No reproduction permitted without written permission from TE.CO. Tecnologia Commerciale S.p.A.